



T:1.6 Dimensions of PC board holes  
Tolerance : ±0.1(Printed-top view)

|           | S JACK  | PIN JACK |
|-----------|---------|----------|
| SCHEMATIC |         |          |
| COLOR     | HOUSING | BLACK    |
|           | WASHER  | YELLOW   |

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

| LTR | PART NAME    | QTY | MATERIAL | REMARK             |
|-----|--------------|-----|----------|--------------------|
| 9   | CONTACT FOOT | 1   | C2680    | MB:Cu Cu/Sn PLATED |
| 8   | SEALED PLATE | 1   | C2680    | MB:Cu Cu/Sn PLATED |
| 7   | AXIS SUPPORT | 1   | C2680    | MB:Cu Cu/Sn PLATED |
| 6   | WASHER       | 1   | ABS      | UL-94HB            |
| 5   | CONTACT FOOT | 2   | C2680    | MB:Cu Cu/Sn PLATED |
| 4   | COAT         | 1   | C2680    | MB:Cu Cu/Sn PLATED |
| 3   | CONTACT FOOT | 1   | C2680    | MB:Cu Cu/Sn PLATED |
| 2   | CONTACT FOOT | 4   | C5191    | MB:Cu Ag PLATED    |
| 1   | HOUSING      | 1   | ABS      | UL-94HB            |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XXX±

DATE

ANG±

SIZE A4

P PROJECTION



ORDER INFORMATION

RCMDB1-FREYL-0204-LF

SERIES

LEADFREE

02 TO 04 WAY

YELLOW

FEMALE TO FEMALE

EAR  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: PIN JACK+S JACK