



PANEL CUT-OUT

SPECIFICATION:

1. INSULATION RESISTANCE: OVER 100MΩ 500V DC.
2. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.
3. Body Materil: Black Glass-Fiber Thermoplastic . UL 94V-2~0
4. FUSEHOLDER SUITABLE 5x20mm FUSE.

Rating: AC 10A 250V	
Mark	Safety Regulation
Ⓢ	3C
Rating: AC 6A 250V	
Mark	Safety Regulation
cULus	cULus

IMPORTANT THIS DRAWING FOR REFERENCE ONLY 注意：此圖只供參考用

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

P PROJECTION



ORDER INFORMATION

ACF-PQ4FSPE33-03V-LF
SERIES | | | | | LEADFREE
MALE | | | | | VERTICAL TERMINAL
TAB 4.8mm | | | | | 03WAY
FUSE | | | | | 3.35 DIA
EAR
PANEL

DESCRIPTION:

www.morethanall.com