

**SPECIFICATION**  
**MATERIAL**  
 Insulator: Polyester resin and glass fiber reinforced (UL94V-0)  
 Contacts: Brass  
**CONTACT PLATING**  
 Contact area: Gold flash  
 Solder tails: 100u" Tin over 40u" Nickel  
**ELECTRICAL**  
 Operation voltage: 250 VAC max.  
 Current rating: 3 Amps max.  
 Contact resistance: 15 mohms max.  
 Insulation resistance: 3000 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 1000 VAC / minute  
 Operating temperature: -55°C TO +105°C

POSITION	A	B	C	D
DFM-PN-09	16.92	25.00	30.8	22.4
DFM-PN-15	25.25	33.30	39.2	30.8
DFM-PN-25	38.96	47.10	53.1	44.5
DFM-PN-37	55.42	63.50	69.4	61.4

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ±  
 ANG ±



**ORDER INFORMATION**

DFM-PN-xx-LF  
 SERIES | LEADFREE  
 | 09-37WAY  
 | NUT  
 | MALE

DESCRIPTION: D-SUB IDC FOR FLAT RIBBON CABLE