

## SPECIFICATIONS

### Electrical

Current Rating: 5A AC, DC

Voltage Rating: 250V AC, DC

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 1000MΩ/ min.

Dielectric Withstanding Voltage: 1500V AC/ min.

Contact Resistance: 10mΩ/ max.

### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	7.50	12.40	VK-H-02	
3	12.50	17.40	VK-H-03	
4	17.50	22.40	VK-H-04	
5	22.50	27.40	VK-H-05	
6	27.50	32.40	VK-H-06	
7	32.50	37.40	VK-H-07	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.10

UNIT / mm

SCALE 1 : 1

.XX ±


DATE

.XXX ±

ANG ±

SIZE A4

PJECTION



ORDER INFORMATION

VK-H-xx-LF  
SERIES | LEADFREE  
02-07 WAY  
HOUSING

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 7.5/5.0mm Wire-to-Board Housing