

RECOMMENDED PCB LAYOUT

Material:

- Item ③ Contact pin: Brass(CuZn) Tin plated
- Item ④ Terminal(housing): Thermoplastic (UL94V-0)

Electrical: cULus

- Voltage rating: 300V
- Current rating: 8A
- Withstanding Voltage: 1.6 KV
- Operating temperature: -40°C to +115°C
- △ Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: us

DIMENSION

A	$N \times 3.81 + 2$
B	$(N-1) \times 3.81$

N= NUMBER OF CONCATS

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION

TBH038-PDB-xx-LF

SERIES | LEADFREE  
| 02~24WAY  
| BOX  
| DIP 180°  
| MALE

DESCRIPTION: