

T:1.6 Dimensions of PC board holes  
Tolerance : ±0.1(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-R40AM-20	φ2.0	
DCJ-R40AM-25	φ2.5	
DCJ-R40AM-165	φ1.65	

LTR	PART NAME	QTY	MATERIAL	REMARK
7	COAT	1	ALOARY	MB:Cu Ni PLATED
6	CONTACT FOOT	1	BRASS	MB:Cu Ni PLATED
5	PIN	1	BRASS	MB:Cu Ni PLATED
4	CONTACT FOOT	1	BRASS	MB:Cu Ag PLATED
3	CURVE PIECE	1	BRASS	MB:Cu Ag PLATED
2	SPRING PIECE	1	BRONZE	MB:Cu Ag PLATED
1	HOUSING	1	PBT	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE


SIZE A4

PJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION



DESCRIPTION: DC POWER JACK

煜倫股份有限公司

www.morethanall.com