


Recommended P.C.B Layout

MATERIAL

Insulator : NYLON 46
Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C



POLES	DIM E	POLES	DIM E
2	1.27	18	21.59
3	2.54	19	22.86
4	3.81	20	24.13
5	5.08	21	25.40
6	6.35	22	26.67
7	7.62	23	27.94
8	8.89	24	29.21
9	10.16	25	30.48
10	11.43	26	31.75
11	12.70	27	33.02
12	13.97	28	34.29
13	15.24	29	35.56
14	16.51	30	36.83
15	17.78	31	38.10
16	19.05	32	39.37
17	20.32	33	40.64

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE


SIZE A4

PPOJECTION

X. ±
.X ± 0.30
.XX ± 0.15
.XXX ±
ANG ±



ORDER INFORMATION



DESCRIPTION: PIN HEADER 1.27*1.27mm RIGHT ANGLE TYPE, SINGLE ROW