



Recommended Hole Dimensions

FEATURES:

- . 2-20 Circuits
- . Housing, UL 94V-2 Nylon 6/6, Natural
- . Designed for parallel and perpendicular board stacking, also for PCB-to-harness PCB-to-chassis connection
- . Mates with .045"[1.14mm] square pins or round pins
- * FOR CIRCUIT SIZES 4 THROUGH 20 ADD .200" OR

SPECIFICATIONS:

- . Current rating: 7A AC, DC
- . Voltage rating: 250V AC, Maximum
- . Temperature range: -40°C ~ +105°C
- . Contact resistance: Initial Value/10mΩ max. After environmental testing /20mΩ max.
- . Insulation resistance: 5000 MΩ min
- . Withstand Voltage: 1500V AC/minute
- . Applicable PC board thickness: .063"[1.6mm]

Dimensional Information

Circuits	Dim.A±.008 0.20	Dim.B±.008 0.20
2	.200 5.08	.400 10.16
3	.400 10.16	.600 15.24
4	.600 15.24	.800 20.32

UNIT: INCH
MM



PART NO. LKX-B-xx

DWG NO. LKX-B-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ±
.XX ±
.XXX ±
AWG

DESCRIPTION: (5.08mm) Center P.C.Board Connectors

AREA

REVISIONS

HK

DATE

煜倫有限公司