



Recommended P.C.B Layout

MATERIAL
 Insulator : 30% Glass fiber PBT
 Contact Pin : Brass

SPECIFICATION
 Current Rate : 1 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

M-D-2Xxx-LF
 LEADFREE
 RoHS Compliant

POLES	DIM E	POLES	DIM E
		23	44.00
2	2.00	24	46.00
3	4.00	25	48.00
4	6.00	26	50.00
5	8.00	27	52.00
6	10.00	28	54.00
7	12.00	29	56.00
8	14.00	30	58.00
9	16.00	31	60.00
10	18.00	32	62.00
11	20.00	33	64.00
12	22.00	34	66.00
13	24.00	35	68.00
14	26.00	36	70.00
15	28.00	37	72.00
16	30.00	38	74.00
17	32.00	39	76.00
18	34.00	40	78.00
19	36.00	41	80.00
20	38.00	42	82.00
21	40.00	43	84.00
22	42.00	44	86.00



PART NO. M-D-2Xxx
 DWG NO. M-D-2Xxx
 FILE NO.
 UNIT / mm SCALE 1:1

APPROVED BY CY
 DRAWING BY
 PROJECTION

TOLERANCES ARE
 .0 = ±.30
 .00 = ±.20
 .000 = ±.XXX
 .0000 = ±.
 ANG. = ±3'

DESCRIPTION: PIN HEADER 2.00*2.00mm STRAIGHT TYPE, DUAL ROWS

AREA	REVISIONS	HK	DATE
------	-----------	----	------

煜倫股份有限公司