

MATERIAL

INSULATOR: GLASS-REINFORCED THERMOPLASTIC (PBT),
UL94V-0 RATED.

CONTACT: COPPER ALLOY.

SOLDER AREA- 120u TIN 50u NICKEL.

COLOR:GREEN

ELECTRICAL

DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VAC RMS.

CURRENT RATING: 3 AMP.

INSULATION RESISTANCE: 5,000 MEG. OHMS MIN. AT 500 VDC.

CONTACT RESISTANCE: 20 MILLI OHMS MAX.

MECHANICAL

INSERTION FORCE: 340 GRAMS MAX PER CONTACT PAIR.

WITHDRAWAL FORCE: 28 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL

TEMPERATURE RANGE: -55° TO +85°.

DIM. Pin NO.	A	B	C	D	E
06	29.94	22.22	14.74	10.34	5.08
14	40.10	32.38	24.9	20.50	15.24
16	42.64	34.92	27.44	23.04	17.78
66	106.14	98.42	90.94	86.54	81.28
86	131.54	123.82	116.34	111.94	106.68
100	149.32	141.60	134.12	129.72	124.46

GE-SLE-xxx-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. GE-SLE-xxx

DWG NO. GE-SLE-xxx

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司