



RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: $\pm 0.05\text{mm}$

CONTACT LENGTH
DIM. FOR "Y":

13	13.0mm
09	9.5mm

POSITION	A	B	C	D
9F	16.30	25.00	30.8	19.2
15F	24.60	33.30	39.2	27.7
19F	30.00	38.86	44.8	32.8
23F	35.30	44.30	50.3	38.3
25F	38.30	47.10	53.1	41.1
37F	54.80	63.50	69.4	57.3

▲ SPECIFICATION
 MATERIAL
 Insulator: Thermal Plastic UL94V-0
 Contacts: Copper Alloy
 Shell: Steel
 Rivet, Boardlock: Copper Alloy
 ▲ CONTACT PLATING
 Underplate: 50u" Nickel
 Contact Area: 5u"~30u" Selective Gold
 ELECTRICAL
 Operation Voltage: 250 VAC Max.
 Current Rating: 3 Amps Max.
 Contact Resistance: 15 mohms Max.
 Insulation Resistance: 3000 Mohms Min @ 500 VDC
 Dielectric Withstanding Voltage: 1000 VAC / Minute
 Operating Temperature: -55°C To +105°C

DDL-Sxx-xx-LF
 LEADFREE
 09:9.5mm
 13:13.0mm

RoHS Compliant



PART NO. DDL-Sxx-xx

DWG NO. DDL-Sxx-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX \pm
AWG

DESCRIPTION:

AREA

REVISIONS

REVISIONS

HK

HK

DATE

DATE

煜倫股份有限公司