

Features:

- Material: UL 94V-2 Nylon 66
- Pin Material: Tin-plated phosphor bronze
- Standard Color: Nature

Specification:

- Current rating: 13A (2~4P), 11A (6~15P)
- Voltage rating: 600V
- Dielectric withstanding voltage: 5000V AC/minute
- Ambient temperature rise: -55°C ~ 105°C
- Operating Temperature Range: -25°C ~ 85°C

UL-PDX-1Xxx-LF
LEADFREE

RoHS Compliant

Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	6.35	13.97	7	38.10	45.72
3	12.70	20.32	8	44.45	52.07
4	19.05	26.67	9	50.80	58.42
5	25.40	33.02	10	57.15	64.77
6	31.75	39.37			

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. UL-PDX-1Xxx

DWG NO. UL-PDX-1Xxx

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司