



T:1.6 Dimensions of PC board holes
Tolerance : ± 0.1 (Printed-bottom view)

6	TERMINAL	1	C2680	t=0.4	MB:Cu Cu/Sn PLATED
5	TERMINAL	1	C2680	t=0.4	MB:Cu Cu/Sn PLATED
4	OUTER CONTACT	1	C2680	t=0.4	MB:Ni Au PLATED
3	COVER	1	ABS		UL-94HB
2	WASHER	1	ABS		UL-94HB
1	HOUSING	1	ABS		UL-94HB(BLACK)
LTR	PART NAME	QTY	MATERIAL		REMARK

RCAB1-JR54E1WRG01-03		
COLOR	A	WHITE
	B	RED
SCHEMATIC	A	○ 2T
	B	○ 1T
		○ S

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

P PROJECTION



ORDER INFORMATION

RCAB1-JR54E1WRG01-03-LF

SERIES JACK DIP90° 5.4mm EAR
LEADFREE 03WAY GOLD 1u" RED WHITE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: PIN JACK