


▽ DIP2 PITCH 2.54MMX7.62MM I.D.C. DIP PLUG
FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

MATERIAL & FINISH
 *INSULATOR:PBT+GLASS FIBER UL 94V-0
 *CONTACT:BRASS
 *FINISH: GOLD-PLATED OVER NICKEL

SPECIFICATIONS
 *CURRENT RATING: 1A AC,DC
 *VOLTAGE RATING: 250V AC,DC
 *TEMPERATURE RANGE: -40°C TO +105°C
 *CONTACT RESISTANCE: 20MΩ MAX
 *INSULATION RESISTANCE: 1,000MΩ MIN
 *WITHSTANDING VOLTAGE: 500V AC/MIN



PART NO	DIM A	DIM B
IP03-C2-08	7.62	15.42
IP03-C2-10	10.16	17.96
IP03-C2-14	15.24	23.04
IP03-C2-16	17.78	25.58
IP03-C2-18	20.32	28.12
IP03-C2-20	22.86	30.66

PART NO	DIM A	DIM B
IP03-C2-24	27.94	35.74
IP03-C2-26	30.48	38.28
IP03-C2-28	33.02	40.82
IP03-C2-34	40.64	48.44
IP03-C2-40	48.26	56.06

DIMENSIONS:MM

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. IP03-C2-xx		CHECKED BY CY		TOLERANCES ARE		DESCRIPTION:					
DWG NO. IP03-C2-xx		DRAWING BY		.X .XX .XXX AWG							
FILE NO.		PROJECTION		AREA		REVISIONS		HK		DATE	
UNIT / mm	SCALE 1:1										