



6	SCREW(short)	2PCS
5	Female Connector	1PCS
4	Plastic assembly shell	2PCS
3	SCREW(long)	2PCS
2	Male Connector	1PCS
1	20AWG*2C+28AWG*5C+Extrusion With Talcum Powder OD6.0MM BLACK	1PCS
Item	Name & Description	Q'TY

CONNECTIONS

P1	COLOUR	P2
1	GREEN	1
2	ORANGE	2
3	BLUE	3
4	PURPLE	4
5	BROWN	5
6	RED	6
7	BLACK	7

Quality Requirement
 Continuity:1Ω(MAX)
 Insulation resistance:10MΩ (MIN)
 Withstand Voltage:0.05Sec DC300V

L	LENGTH
L1	1500±30
L2	2500±50
L3	3000±50

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

TOLERANCES ARE

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

DWX2-07W22028-Exxx-LF

SERIES

07W2

LEADFREE

1M5:1.5 METER

2M5:2.5 METER

3M :3 METER

MALE TO FEMALE

20/28 AWG

DESCRIPTION: