

**Material:**

1. Insulator: PBT+30% Glass Fiber(Meet UL94V-0).
2. Contact: Copper Alloy.
3. Contact Plated: Selective Gold over Nickel Plated.
4. Shell: Steel with Nickel or Tin or Zinc Plated.

**Specification:**

1. Current Rating: 5 Amps.
2. Withstanding Voltage: AC 500V for 1 Minute.
3. Insulation Resistance: 1000MΩ Min. at DC 500V.
4. Contact Resistance: 15mΩ Max..
5. Operating Temperature: -40°C~+105°C.

No. of Contacts	Dim. A	Dim. B	Dim. C	Dim. D
DRM-SGN-09	16.33	24.99	30.81	11.08
DRM-SGN-15	24.66	33.32	39.14	19.39
DRM-SGN-25	38.38	47.04	53.04	33.24
DRM-SGN-37	54.84	63.50	69.32	49.86

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES


DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION



**ORDER INFORMATION**

DRM-SGN-xx-LF  
SERIES | LEADFREE  
09~37WAY  
NUT  
FULL GOLD  
FEMALE

DESCRIPTION: D-S-sub Male Right Angle Connector Footprint 10.20mm Clinch Nut/Screw Lock Type