

RECOMMENDED PC BOARD LAYOUT  
WITHOUT MOUNTING POSTS

**MATERIAL & FINISH**

- |                  |                             |
|------------------|-----------------------------|
| ① CENTER CONTACT | : BRONZE GOLD PLATING       |
| ② BODY           | : ZINC ALLOY NICKEL PLATING |
| ③ HOUSING        | : PBT (94 V-0) WHITE        |
| ④ INSULATOR      | : PE-606                    |
| ⑤ MOUNTING POST  | : BRONZE, TIN PLATING       |
| ⑥ SOLDER TAIL    | : COPPER WIRE, TIN PLATING  |
| ⑦ WASHER         | : STEEL, NICKEL PLATING     |
| ⑧ NUT            | : BRASS, NICKEL PLATING     |

RECOMMENDED MOUNTING HOLE  
MAXIMUM PANEL THICKNESS: 5.5MM

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY


CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

BNC-JR15WWH-50-LF  
SERIES | | | | LEADFREE  
50 OHM  
WHITE  
WASHER+NUT  
HIGH 15.8mm  
DIP 90°  
JACK

DESCRIPTION: