

SPECIFICATIONS

BARRIER MATERIAL: THERMOPLASTIC (UL 94V-0).BLACK
 TERMINALS: TIN PLATED BRASS
 SCREW: NICKEL PLATED STEEL
 WIRE RANGE:18-22 STR
 RATING: 10 AMPERES,300VAC
 INSULATION WITHSTANDS VOLTAGE AC 2000V
 INSULATION RESISTANCE 500M OR MORE AT DC 500V

DIMENSION:±0.5

| POLE | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| A | 16.76 | 24.38 | 32 | 39.62 | 47.24 | 54.86 | 62.48 | 70.1 | 77.72 |
| B | 7.62 | 15.24 | 22.86 | 30.48 | 38.1 | 45.72 | 53.34 | 60.96 | 68.58 |
| POLE | 11 | 12 | 13 | 14 | 15 | 17 | 18 | 19 | 20 |
| A | 85.34 | 92.96 | 100.6 | 108.2 | 115.8 | 131.06 | 138.68 | 146.3 | 153.92 |
| B | 76.2 | 83.82 | 91.44 | 99.06 | 106.7 | 121.92 | 129.54 | 137.16 | 144.78 |
| POLE | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 |
| A | 161.54 | 169.16 | 176.78 | 184.4 | 192.02 | 199.64 | 207.3 | 214.9 | 222.5 |
| B | 152.4 | 160.02 | 167.64 | 175.26 | 182.88 | 190.5 | 198.1 | 205.7 | 213.4 |
| POLE | 30 | 31 | 32 | | | | | | |
| A | 230.1 | 237.7 | 245.4 | | | | | | |
| B | 221 | 228.6 | 236.2 | | | | | | |



煜倫股份有限公司


www.morethanall.com

RoHS Compliant

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT/mm SCALE 1:1
 DATE
 SIZE A4 PROJECTION

TOLERANCES ARE

X.±
 .X±
 .XX±
 .XXX±
 ANG±



ORDER INFORMATION

TBB076-D15-xx-LF
 SERIES | LEADFREE
 02~32WAY
 PIN LONG 15.0mm
 DIP 180°

DESCRIPTION: PITCH 7.62 mm