

T:1.6 Dimensions of PC board holes
Tolerance : ± 0.1 (Printed-bottom view)

	S JACK	PIN JACK	
SCHEMATIC			
COLOR	BLACK	WASHER	
		HOUSING	ORANGE

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

12	HOUSING(S JACK)	1	ABS	UL-94HB
11	CENTER CONTACT	1	2680 t=0.4	MB:Cu Cu/Sn PLATED
10	EARTH FITTING	1	2680 t=0.4	MB:Cu Cu/Sn PLATED
9	TERMINAL	1	5210 t=0.4	MB:Cu Ag PLATED
8	TERMINAL	1	5210 t=0.4	MB:Cu Ag PLATED
7	TERMINAL	1	5210 t=0.4	MB:Cu Ag PLATED
6	TERMINAL	1	5210 t=0.4	MB:Cu Ag PLATED
5	GROUND CONTACT	1	5191 t=0.3	MB:Cu Cu/Sn PLATED
4	SHIELDED PLATE	1	SPCC t=0.3	MB:Cu Cu/Sn PLATED
3	OUTER CONTACT	1	2680 t=0.4	MB:Cu Cu/Sn PLATED
2	WASHER	1	ABS	UL-94HB
1	HOUSING(PIN JACK)	1	ABS	UL-94HB
LTR	PART NAME	QTY	MATERIAL(THICK,COLOR)	REMARK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, \pm

CHECKED BY GENIUS

.X, \pm

UNIT / mm

SCALE 1 : 1

.XX, \pm


DATE

.XXX, \pm

ANG, \pm

SIZE A4

P PROJECTION



ORDER INFORMATION

RCMDB1-FRHOR-0204-LF

SERIES

LEADFREE

02 TO 04 WAY

ORANGE

FEMALE TO FEMALE

HOLE
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: PIN JACK+S JACK