



額定電壓	DC絕緣300V / AC絕緣300V
工作頻率	DC / AC60Hz
絕緣阻抗	DC絕緣 100.0MΩ / AC2.00mA
皮線規格	Composition : 7/ 0.127 / Thickness : 0.9mm
工作電流	0.5Amp
用途	通訊
所力最大扭力	5kg

A	UL2651 #28 *10P PH=1.0mm GRAY
T1	IDC SOCKET PH=2.0mm MF-C3-10 (三件式)
T2	IDCDIP PULG PH=2.0mm MIP-C2-10 PCB + 氣泡袋(保護)

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4

P PROJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

MF3MIP-1010-Axxx-LF

SERIES

LEADFREE

14C:14 CM  
22C:22 CM

FEMALE TO MALE  
10PIN TO 10 PIN

DESCRIPTION: