


NO.	NAME	MATERIAL	FINISH	Q'TY
1	EARTH TERMINAL	PBS T:0.25	TIN PLATED	1
2	RING SPRING	PHOS. BRONZE T:0.25	TIN PLATED	1
3	RING SHUNT	BRASS T:0.25	TIN PLATED	1
4	TIP SPRING	PBS T:0.20	TIN PLATED	1
5	RING SHUNT	PHOS. BRONZE T:0.25	TIN PLATED	1
6	TIP SPRING	PHOS. BRONZE T:0.25	TIN PLATED	1
7	HOUSING	NYLON PA9T G.F.	SEE COLOR	1
8	SHELL	PBS T:0.20	NICKEL PLATED	1

MODEL NO.	PJ-R30Scc-06C (PC99 COLOR)					
	PK	BK	LM	YL	OR	LB
HOUSING COLOR	PINK	BLACK	LIME	YELLOW	ORANGE	LIGHT BLUE
PANTONE	701C		577C	123C	157C	284C

**Specification:**

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.  
 Insulation Resistance: 100M Ohm Min. At 500V DC.  
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.  
 Dielectric Withstanding Voltage: 500V AC For 1 Minute.  
 Durability (Life Test): A: For Phosphor Bronze 1500 Cycles Minimun.  
 Insertion Force: 0.3~3.0 Kg.  
 Extraction Force: 0.3~3.0Kg.



**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±  
.X ± 0.25  
.XX ± 0.13  
.XXX ± 0.05  
ANG ±

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

P PROJECTION



**ORDER INFORMATION**

**PJ-R30Scc-06C-LF**  
 SERIES | 6P3C | LEADFREE  
 DIP 90° | PK:PINK | BK:BLACK | LM:LIME | YL:YELLOW | OR:ORANGE | LB:LIGHT BLUE  
 POST 3.5mm | SPRING

DESCRIPTION: φ3.5 EARPHONE JACK FLAT 6 PIN DIP

**煜倫股份有限公司**

www.morethanall.com