

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 1000M Ω Min
 Withstanding Voltage: 1800V AC/minute
 Material: Nylon66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

| PART NO. | Dimensions | |
|----------|------------|-------|
| | A | B |
| BH-H-02 | 4.00 | 9.80 |
| BH-H-03 | 8.00 | 13.80 |
| BH-H-04 | 12.00 | 17.80 |
| BH-H-05 | 16.00 | 21.80 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm



ORDER INFORMATION

BH-H-xx-LF
 SERIES | LEADFREE
 02-05 WAY
 HOUSING

DESCRIPTION: 4.00mm PITCH HOUSING