



▽ DIP3 PITCH 2.54MMX15.24MM I.D.C. DIP PLUG
FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

MATERIAL & FINISH
 *INSULATOR:PBT+GLASS FIBER UL 94V-0
 *CONTACT:BRASS
 *FINISH: GOLD-PLATED OVER NICKEL

SPECIFICATIONS
 *CURRENT RATING: 1A AC,DC
 *VOLTAGE RATING: 250V AC,DC
 *TEMPERATURE RANGE: -40°C TO +105°C
 *CONTACT RESISTANCE: 20MΩ MAX
 *INSULATION RESISTANCE: 1,000MΩ MIN
 *WITHSTANDING VOLTAGE: 500V AC/MIN

PART NO	DIM A	DIM B
IP06-C2-10	10.16	17.96
IP06-C2-14	15.24	23.04
IP06-C2-16	17.78	25.58
IP06-C2-18	20.32	28.12
IP06-C2-20	22.86	30.66
IP06-C2-24	27.94	35.74

PART NO	DIM A	DIM B
IP06-C2-26	30.48	38.28
IP06-C2-28	33.02	40.82
IP06-C2-32	38.10	46.00
IP06-C2-34	40.64	48.44
IP06-C2-36	43.18	50.98
IP06-C2-40	48.26	56.06

DIMENSIONS:MM



PART NO. IP06-C2-xx

DWG NO. IP06-C2-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

IDC DIP PLUG
PITCH2.54mm*15.24mm

煜倫股份有限公司

FILE NO.

DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION