


Specification:

Contact Resistance: 30m Ohm. Max At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
 Dielectric Withstanding Voltage: 500V AC For 1 Minute.
 Durability (Life Test): 1500 Cycles Minimum.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0Kg.



NO.	NAME	MATERIAL	FINISH	Q'TY
1	GROUND PIN	BRASS T: 0.30	GOLD PLATED	1
2	RING SPRING	PBS T:0.25	TIN PLATED	1
3	TIP BREAK	PBS T:0.25	TIN PLATED	1
4	RING BREAK	PBS T:0.30	TIN PLATED	1
5	BUSHING	PBS T:0.25	TIN PLATED	1
6	SPRING	PBS T:0.30	TIN PLATED	1
7	SPRING	STAINLESS STEEL		1
8	HOUSING	NYLON PA9T	BLACK	1

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.38

.X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG ±

P PROJECTION



ORDER INFORMATION

PJ-R32-06-LF
 SERIES | LEADFREE
 06 WAY
 POST 3.0+2.7mm
 DIP 90°

DESCRIPTION: 3.5mm EARPHONE JACK FLAT 5 PIN DIP