



Specifications:

Current Rating:1.0A AC/DC

Voltage Rating:30V AC/DC

Contact Resistance:20m ohm. Max.

Insulation Resistance:1000M ohm. Min.

Withstanding Voltage:500V AC For One Minute

Operating Temperature Range:-40°C ~ +105°C

Material and Finish

Insulator:High Temp. Plastic (UL94V-0)

Contact:Copper Alloy

Finish:Tin Plated

Circuits	Dimension		Circuits	Dimension	
	A	B		A	B
4	8.45	2.54	16	23.69	17.78
6	10.99	5.08	18	26.23	20.32
8	13.53	7.62	20	28.77	22.86
10	16.07	10.16	22	31.31	25.40
12	18.61	12.70	24	33.85	27.94
14	21.15	15.24	26	36.39	30.48

MIM-BC-xx-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MIM-BC-xx

DWG NO. MIM-BC-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

2.54mm IDC Connector Male
On Wire Type

煜倫股份有限公司

FILE NO.

DRAWING BY

.X±0.2
.XX±0.1
.XXX±
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION

