



Specifications:

- 1.Electrical:
- 1-1 Rating: AC 5V/0.5A
 - 1-2 Contact Resistance: 50m Ohm or less
 - 1-3 Insulation Resistance: 100M Ohm Min at DC500V
 - Δ 1-4 Dielectric Withstanding Voltage: AC 100V for 1 minute(Cut-off: 0.5mA)
- 2.Mechanical:
- 2-1 Insertion force: 35N (3.57kgf) max.
 - 2-2 Withdrawal Force: 1N (0.1kgf) min.

NOTE:

- 1.MATERIAL
- 1-1 CONTACT: PHOSPHOR BRONZE
 - 1-2 HOUSING: LCP
 - 1-3 SHELL: PHOSPHOR BRONZE
- 2.PLATING
- 2-1 CONTACT: GOLD 10u"
 - 2-2 SHELL: GOLD FLASH 1-3u"

PCB LAYOUT



PART NO. MSB-SW-8A		CHECKED BY CY		TOLERANCES ARE .X±0.2 .XX± .XXX± AWG	DESCRIP TION: MINI USB 8PIN (F) 單排 DIP 單缺口			
DWG NO. MSB-SW-8A		DRAWING BY			AREA	REVISIONS	HK	DATE
FILE NO.		PROJECTION						
UNIT / mm	SCALE 1:1							

煜倫股份有限公司