



P.C.B LAYOUT

NO. OF CONTACT	Dimension		NO. OF CONTACT	Dimension	
	A	B		A	B
02	3.96	8.06	10	35.64	39.74
03	7.92	12.02	11	39.60	43.70
04	11.88	15.98	12	43.56	47.66
05	15.84	19.94	13	47.52	51.62
06	19.80	23.90	14	51.48	55.58
07	23.76	27.86	15	55.44	59.54
08	27.72	31.82	16	59.40	63.50
09	31.68	35.78			

**NOTES:**

**SPECIFICATION**

1. Current : 5A max.
2. Voltage: 250V AC max.
3. Insulation Resistance: 1000 MΩ min.
4. Contact Resistance: 10mΩ max.
5. Dielectric Withstanding Voltage: 1500V AC
6. Temperature: -40°C to +105°C

**MATERIAL**

1. Contact: Brass
2. Housing: Nylon, UL 94V-2
3. Plated: Tin Plating(Lead Free)

**KX-B-xx-LF**  
LEADFREE

**RoHS Compliant**



PART NO. **KX-B-xx**

DWG NO. **KX-B-xx**

FILE NO.

UNIT / mm SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

- .X ± 0.2
- .XX ±
- .XXX ±
- AWG

DESCRIP TION:				
	AREA	REVISIONS	HK	DATE

煜倫股份有限公司