

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mW Max.
4. Insulation resistance: 1000 MW Min at DC 500V.
5. Temperature range: -55°C~+105°C

MSB-PM-5B-LF
LEADFREE
RoHS Compliant

3	Shell	1	Cold rolled steel	T=0.30mm	80u"~120u" Nickel Plated
2	Contact	5	Brass	T=0.25mm	Contact area: 0.8~1.2u"Gold Plated over 40u"Nickel min Solder area: 80~120u"Tin Plated over 40u"Nicked Min.
1	Housing	1	PBT	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. **MSB-PM-5B**

DWG NO. **MSB-PM-5B**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIP TION: MINI USB-5PIN(M) B TYPE SOLDER 短鐵殼

AREA

REVISIONS

HK

DATE

煜倫股份有限公司