



MATERIAL & FINISH

- *precision swiss screw machine contact tap entry for easy insertion.
- *4 fingers contact for very low insertion force.
- *resistance to solder heat : Up to 260^o C 1 minute without any plastic deformation.
- *Insulator: Polyphenylene sulphide (PBT) UL 94V-0
- *standard color:black
- *contact:inner clip,beryllium copper. 5u"/ 10u' or 30u', gold over 50u" nickel.
- Outer sleeve, brass, 150u" tin over 50u" nickel or 10u" gold over nickel.
- *contact resistance:Max. 10 Milliohm
- *Insulation resistance: 5000 Mege Ohm at 500 VDC.
- *Dielectric Withstanding voltage: 1000 VAC (RMS) minimum.
- *Temperature rating: -55^o C to +175^o C

SS-R70-1Xxx-LF
 LEADFREE
 HEIGHT 70: 7.0mm

RoHS Compliant



PART NO. **SS-R70-1Xxx**

DWG NO. **SS-R70-1Xxx**

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIP TION:

AREA	REVISIONS	HK	DATE
------	-----------	----	------

煜倫股份有限公司