


Right Angle



- Features:
- * Available in 3 through 15 circuits
 - * Material: Insulator: Nylon 66 UL 94V-0
Contact: Phosphor Bronze, tin plated
 - * Box-shaped shrouded

XH-SR-xx-LF
LEADFREE

RoHS Compliant

Dimensional & Ordering Information:

Circuits	Part No	Dimensions			PCS/BOX
		A	B	C	
3	XH-SR-03	5.00	10.00	8.20	500
4	XH-SR-04	7.50	12.50	10.70	500
5	XH-SR-05	10.00	15.00	13.20	500
6	XH-SR-06	12.50	17.50	15.70	500
7	XH-SR-07	15.00	20.00	18.20	250
8	XH-SR-08	17.50	22.50	20.70	250
9	XH-SR-09	20.00	25.00	23.20	250
10	XH-SR-10	22.50	27.50	25.70	250
11	XH-SR-11	25.00	30.00	28.20	200
12	XH-SR-12	27.50	32.50	30.70	200
13	XH-SR-13	30.00	35.00	33.20	200
14	XH-SR-14	32.50	37.50	35.70	100
15	XH-SR-15	35.00	40.00	38.20	100



PART NO. XH-SR-xx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± 0.1 .XXX ± AWG	DESCRIP TION:			
DWG NO. XH-SR-xx		DRAWING BY						
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1							

煜倫股份有限公司