

Recommend P.C.B Layout Tolerance±0.05

1. MATERIAL :
  - 1-1. HOUSING : LCP UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : PHOSPHOR BRONZE
  - 1-3. SHELL : STAINLESS
2. FINISH :
  - 2-1. CONTACT :
    - CONTACT AREA : 10 MICRO INCHES MIN. GOLD PLATED
    - SOLDER AREA : BRIGHT TIN
    - UNDER PLATE : NICKEL
  - 2-2. SHELL : NICKEL PLATED
3. ELECTRICAL SPECIFICATION :
  - 3-1. RATED CURRENT : 0.5A
  - 3-2. RATED VOLTAGE : AC 30Vr.m.s
4. ENVIRONMENTAL :
  - 4-1. OPERATION TEMPERATURE : -25°C~75°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY


CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±  
.X ± 0.20  
.XX ± 0.10  
.XXX ± 0.05  
ANG ± 1°



ORDER INFORMATION

PCM-JWMM-10-LF  
SERIES | LEADFREE  
10 WAY  
METAL FOOT  
90°SMT  
JACK

DESCRIPTION: PCMCIA 10(F) SMT H:5.6