

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mW Max.
4. Insulation resistance: 1000 MW Min at DC 500V.
5. Temperature range: -55°C~+105°C

3	Shell	1	Cold rolled steel	T=0.30mm	80u"~120u" Nickel Plated
2	Contact	5	Brass	T=0.25mm	Contact area: 0.8~1.2u" Gold Plated over 40u" Nickel min Solder area: 80~120u" Tin Plated over 40u" Nicked Min.
1	Housing	1	PBT	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

MSB-PM-5B-LF
SERIES | LEADFREE
5 PIN B TYPE
MOLDING
MALE

DESCRIPTION: MINI USB-5PIN(M) B TYPE SOLDER 短鐵殼