

PCB LAYOUT

NOTES:

- 1.HOUSING: MATERIAL: LCP+30%GF UL 94V-0
- 2.SHELL: MATERIAL: BRASS C2680R-H T=0.25±0.01.
FINISH: 120μ" BRIGHT TIN PLATED AND
50μ" MIN NI UNDERPLATED ON ENTIRE CONTACT.
- 3.CONTACT: MATERIAL: BRASS C2680R-H T=0.2±0.01.
FINISH: 3μ" MIN GOLD FLASH ON AREA
120μ" MIN TIN PLATED ON SOLDER TAIL AND
50μ" MIN NI UNDERPLATED ON ENTIRE CONTACT.
- 4.GENERAL TOLERANCE: ±0.10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.38

UNIT / mm

SCALE 1 : 1

.XX ± 0.25


DATE

.XXX ± 0.13

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

MSB-SW-8C-LF
SERIES | LEADFREE
8 PIN C TYPE
90°SMT
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: