



NO	DESCRIPTION	MATERIAL	FINISH	QTY
6	WASHER	IRON	NICKEL	1
5	UNT	IRON	NICKEL	1
4	INSULATOR	DELTRIN	WHITE	1
3	INSULATOR	DELTRIN	WHITE	1
2	PIN	BRASS	TIN	1
1	BODY	ZINC	NICKEL	1

R

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT/ mm    SCALE 1:1  
DATE

0.5-5    =±0.2  
5-30    =±0.4  
30-120   =±0.6  
120-315 =±1  
315-1000 =±1.6  
1000-2000 =±2.4



**ORDER INFORMATION**

**FX2-FSPBNW-75-LF**  
SERIES    LEADFREE  
75 OHM  
NUT+WASHER  
PANEL BACK  
FEMALE TO FEMALE

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

SIZE A4    PROJECTION

DESCRIPTION: F DOUBLE FEMALE(ZINC)

# F CONNECTOR

## ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: AC 1500V

WITH STANDING VOLTAGE: AC 500V ONE MINUTE

INSULATION RESISTANCE: 500MΩ MIN AT DC 500V

CONTACT RESISTANCE: MAX 5mΩ AT DC 1A

IMPEDANCE: 75Ω NOMINAL

VSWR: 1.5MAX. 0-1,000 MHZ

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm

SCALE 1:1

DATE

SIZE A4

P PROJECTION

0.5-5	±0.2
5-30	±0.4
30-120	±0.6
120-315	±1
315-1000	±1.6
1000-2000	±2.4



ORDER INFORMATION

FX2-FSPBNW-75-LF  
SERIES | 75 OHM | LEADFREE  
NUT+WASHER  
PANEL BACK  
FEMALE TO FEMALE

DESCRIPTION: F DOUBLE FEMALE(ZINC)

www.morethanall.com