



**Features:**

- \* Available in 3 through 15 Circuits
- \* Nylon 66 94V-0
- \* 0.50mm(.020")Tin-plated Flash Square Pin
- \* Contact: Brass, Tin-plated

**Specifications:**

- \* Pitch Between Poles 2.0mm
- \* Rated Voltage 250V AC, DC
- \* Rated Current 2A
- \* Withstand Voltage 800V AC/minute
- \* Insulation Resistance 1,000M $\Omega$ /min
- \* Temperature Range -25~85 $^{\circ}$ C

Circuit	Part No	Dimension mm	
		A	B
3	YH20-D-03	4.00	8.00
4	YH20-D-03	6.00	10.00
5	YH20-D-03	8.00	12.00
6	YH20-D-03	10.00	14.00
7	YH20-D-03	12.00	16.00
8	YH20-D-03	14.00	18.00
9	YH20-D-03	16.00	20.00
10	YH20-D-03	18.00	22.00
11	YH20-D-03	20.00	24.00
12	YH20-D-03	22.00	26.00
13	YH20-D-03	24.00	28.00
14	YH20-D-03	26.00	30.00
15	YH20-D-03	28.00	32.00



煜倫有限公司

PART NO. YH20-D-xx

DWG NO. YH20-D-xx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X  
.XX  
.XXX  
AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE