


PCB LAYOUT
(BOTTOM VIEW)

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S. T:0.30	NICKEL PLATED	2
2	INSERT RING	PBT G.F.	BLACK.RED	2
3	INSULATOR	PBT G.F.	WHITE	2
4	CENTER PIN	BRASS T:0.25	TIN PLATED	2
5	FRAME	C.R.S. T:0.60	NICKEL PLATED	1



Specification:


Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V, 2A Max ; AC 100V, 1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0 Kg.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 焯倫股份有限公司
 www.morethanall.com

DRAWING BY CY	X. ± 0.38
CHECKED BY GENIUS	.X ± 0.25
UNIT / mm	.XX ± 0.13
SCALE 1 : 1	.XXX ± 0.05
DATE	ANG ±
SIZE A4	PPOJECTION



ORDER INFORMATION

RCAB1-JR52E0KR-03-LF
 SERIES JACK DIP 90° 5.2mm
 LEADFREE 03WAY RED BLACK NON EAR

DESCRIPTION: RCA JACK