



T:1.6 Dimensions of PC board holes

Tolerance : ± 0.1 (Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-ROP-10	$\phi 1.0$	
DCJ-ROP-13	$\phi 1.3$	

6	PIN	1	H59 BRASS	MB:Cu Ni PLATED
5	CURVE PIECE	1	H62 BRASS	MB:Cu Ag PLATED
4	FLAT PIECE	1	H62 BRASS	MB:Cu Ag PLATED
3	SPRING PIECE	1	STAINLESS STEEL/65Mn STEEL	MB:Cu Ag PLATED
2	COVER	1	PBT/PA66/ABS	
1	HOUSING	1	PBT/PA66/ABS	
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm



ORDER INFORMATION

DCJ-ROP-xx-LF

SERIES

LEADFREE

10:1.0 ϕ
13:1.3 ϕ

OPEN
DIP 90°

DESCRIPTION: DC POWER JACK