

Model No.	POS.1	POS.2	POS.3
	5MS1	ON	NONE
Term. Comm.	2-1	N/A	2-3
SCHEMATIC			

SWITCH FUNCTION

**SPECIFICATIONS**

**MECHANICAL LIFE:** 30,000 make-and-break cycles.  
**CONTACT RESISTANCE:** 10mΩ max. initial @ 2-4VDC  
 100mA for both silver and gold plated contacts.  
**INSULATION RESISTANCE:** 1,000MΩ min.  
**DIELECTRIC STRENGTH:** 1,000 V RMS@sea level.  
**OPERATING TEMPERATURE:** -30°C to 85°C.

**MATERIALS**

**CASE:** Dially phthalate (DAP) (UL94v-0).  
**ACTUATOR:** Nylon, black std.  
**HOUSING:** Stainless Steel.  
**CONTACT:** Silver or gold plated.  
**TERMINAL SEAL:** Epoxy.

**RATING :**

Q : 2Amps @250VAC  
 5Amps @120 VAC or 28 VDC

**CONTACT:** Silver Plated

**RoHS Compliant**

TOLERANCES ARE




煜倫股份有限公司

www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

X. ± 0.30  
 .X ± 0.40  
 .XX ± 0.25  
 .XXX ±  
 ANG ±



**ORDER INFORMATION**

SLSW47-RM047-1X03-LF

SERIES | LEADFREE  
 03 WAY  
 LONG 4.7mm  
 METAL  
 DIP 90°

DESCRIPTION: Slide Switches