



規格
SPECIFICATIONS

- 額定
1. RATING : 10A 250VAC
- 耐電壓
2. WITHSTAND VOLTAGE : AC 2000V 1Min
- 絕緣電阻
3. INSULATION RESISTANCE : MORE THAN 100M (at DC 500V)
- △ 操作溫度
4. OPERATING TEMPERATURE : -25° C TO +85° C (MAX)
- △ 認可安規 : 5. SAFETY

ACF-PQ4FSSWPE-03-LF
LEADFREE
RoHS Compliant

7A	CONNECTOR	1	Bsp1-1/2H	t=0.8	Sn-plated
6B	FUSE HOLDER	1	Bsp1-1/2H	t=0.8	Sn-plated
6A	FUSE HOLDER(SHORT)	1	Bsp1-1/2H	t=0.5	Sn-plated
4F	CONNECTION TERMINAL	2	Bsp1-1/2H	t=0.8	Sn-plated
3B	CENTER TERMINAL	1	Bsp1-1/2H	t=2.0	Sn-plated
2B	EDGE TERMINAL	2	Bsp1-1/2H	t=2.0	Sn-plated
1J	FUSE COVER	1	Nylon#66	94v-2	
1K	BODY	1	Nylon#66	94v-2	



PART NO. ACF-PQ4FSSWPE-03

DWG NO. ACF-PQ4FSSWPE-03

FILE NO.

UNIT / mm SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

- .X ± 0.2
- .XX ±
- .XXX ±
- AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司