

PCB LAYOUT

1. Specification:

- Contact Current Rating: 3Amperes.
- Dielectric Withstanding Voltage: AC 500V at sea level.
- Insulation Resistance: 1000Megohms Min.
- Contact Resistance: 25Milliohms Max.
- Operation Temperature : -55°C to +105°C.

2. Material:

- Contact :Copper Alloy.
- Insulator: (Option PBT/PA6T/LCP/PA9T)
- Shell: SPCC.
- Screw: Copper Alloy.

No.	A	B	C	D	E
15	16.92	24.99	30.81	19.23	2.29
26	25.25	33.32	39.14	27.56	2.29
44	38.96	47.04	53.04	41.28	2.29
62	55.42	63.50	69.32	57.33	2.41

No.	F	H
15	1.145	7.04
26	1.145	6.88
44	1.145	6.88
62	1.205	7.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.25
.XXX ± 0.15
ANG ± 2°

PPOJECTION



ORDER INFORMATION

HDD-PGBKZ-xx-NF
SERIES | | | NON LEADFREE
| | | 15~62 WAY
| | | ZINC
| | | BLACK
| | | FULL GOLD
| | | MALE

DESCRIPTION: D-SUB (H-D),180°,MALE,DIP

煜倫股份有限公司

www.morethanall.com