



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 100V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 800V AC/minute  
 Material: Nylon 66,UL94V-0

**CT-H-xx-LF**  
 LEADFREE

**RoHS Compliant**

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
CT-H-02	2.00	6.00
CT-H-03	4.00	8.00
CT-H-04	6.00	10.00
CT-H-05	8.00	12.00
CT-H-06	10.00	14.00
CT-H-07	12.00	16.00
CT-H-08	14.00	18.00
CT-H-09	16.00	20.00
CT-H-10	18.00	22.00
CT-H-11	20.00	24.00
CT-H-12	22.00	26.00
CT-H-13	24.00	28.00
CT-H-14	26.00	30.00
CT-H-15	28.00	32.00



PART NO. <b>CT-H-xx</b>	
DWG NO. <b>CT-H-xx</b>	
FILE NO.	
UNIT / mm	SCALE 1:1

CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG
DRAWING BY	
PROJECTION	

DESCRIP TION:	2.00mm PITCH HOUSING			
	AREA	REVISIONS	HK	DATE

焯倫股份有限公司