



- Material:
1. Insulator: PBT+30% Glass Fiber(Meet UL94V-0).
 2. Contact: Copper Alloy.
 3. Contact Plated: Selective Gold over Nickel Plated.
 4. Shell: Steel with Nickel or Tin or Zinc Plated.
- Specification:
1. Current Rating: 5 Amps.
 2. Withstanding Voltage: AC 500V for 1 Minute.
 3. Insulation Resistance: 1000MΩ Min. at DC 500V.
 4. Contact Resistance: 15mΩ Max..
 5. Operating Temperature: -40°C~+105°C.

No. of Contacts	Dim. A	Dim. B	Dim. C	Dim. D
DR-PGN-09	16.92	24.99	30.81	11.08
DR-PGN-15	25.25	33.32	39.14	19.39
DR-PGN-25	38.96	47.04	53.04	33.24
DR-PGN-37	55.42	63.50	69.32	49.86

DR-PGN-xx-LF
LEADFREE POSITION

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. DR-PGN-xx

DWG NO. DR-PGN-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION: D-SUB RIGHT ANGLE MALE CONNECTOR
8.08mm WITH RIVET TYPE

FILE NO.

DRAWING BY

.X ± 0.3
.XX ± 0.15
.XXX
AWG

AREA	REVISIONS	HK	DATE
------	-----------	----	------

焯倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION