



Recommended Hole Dimensions

FEATURES:

- . 2-20 Circuits
- . Housing, UL 94V-2 Nylon 6/6, Natural
- . Designed for parallel and perpendicular board stacking, connection
- . Mates with .045"[1.14mm] square pins
- \* FOR CIRCUIT SIZES 4 THROUGH 20 ADD .200" OR

SPECIFICATIONS:

- . Current rating: 7A AC. DC
- . Voltage rating: 250V AC. Maximum
- . Temperatur range: -40°C ~ +105°C
- . Contact resistance: Initial Value/10mΩ max. After environmental testing /20mΩ max.
- . Insulation resistance: 5000 MΩ min
- . Withstand Voltage: 1500V AC/minute
- . Applicable PC board thickness: .063"[1.6mm]

Dimensional Information

Circuits	Dim.A±.008 0.20	Dim.B±.008 0.20
2	.200 5.08	.400 10.16
3	.400 10.16	.600 15.24
4	.600 15.24	.800 20.32

UNIT: INCH  
MM



煜倫有限公司

PART NO. LKX-T-xx		CHECKED BY CY		TOLERANCES ARE		DESCRIP TION: ( 5.08mm ) Center P.C.Board Connectors				
DWG NO. LKX-T-xx		DRAWING BY		.X ± .XX ± .XXX ± AWG						
FILE NO.		PROJECTION		⊕		AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1									