

NOTE:

1.SAFETY:

- 1-1.RATING: 0.5A/250Vac.
- 1-2.CONTACT RESISTANCE: 30mOhm MAX.
- 1-3.INSULATION RESISTANCE: 100Mohm MIN.
- 1-4.DIELECTRIC WITHSTANDING VOLTAGE: 100Vac/1minute.
- 1-5.DURABILITY: 10,000cycles.

2.MATERIAL:

- 2-1.PIN:PHOSPHOR BRONZE.
- 2-2.HOUSING:LCP UL 94-V0 rated
- 2-3.LATCH:STAINLESS #301
- 2-4.SHELL:STAINLESS #301

3.PLATING:

- 3-1.PIN:GOLD FLASH MIN ON CONTACT AREA.

MISB-PS-5A-LF  
LEADFREE  
RoHS Compliant

BOM	
5	CONTACT
2	SHELL
1	HOUSING
數量	零件

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. MISB-PS-5A

DWG NO. MISB-PS-5A

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIPTION: MICRO USB 5PATYPE MALE SOLDER

AREA

REVISIONS

HK

DATE

煜倫股份有限公司