



P.C.B. LAYOUT

N = Number of poles
 Dim A = N x 9.52
 Dim B = (N - 1) x 9.52

	Dim A	Dim B
2-6p	±0.20	±0.20
7-11p	±0.30	±0.30
12-16p	±0.40	±0.40

Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Contacts: Brass
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- △ ● Current rating: 30A
- Wire range:
- △ ● Solid wire(AWG): 10-24
- △ ● Stranded wire(AWG): 10-24
- △ ● Torque(Lb-In): 8.9
- Screw: M3.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 245°C±10°C/5 Sec
- Safety Approval: us

TBH095-A21-xx-LF
 LEADFREE
 RoHS Compliant



PART NO. TBH095-A21-xx

DWG NO. TBH095-A21-xx

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE
 .X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION