

## MATERIAL:

INSULATOR :Hi-temp PPS. UL 94V-0, 240°C

Contact material:phosphor bronze JIS 5210

Contact Platred :150μ"tin over 40μ"nickel

## SPECIFICATIONS:

Temperature range:-50°C to 105°C

CURRENT Rating :1 AMP

Capacitance:1.0 Picoforads (Max)

Contact resistance:30 Milliohms (Max)

Insulation Resistance :1000 Megohms (Min)

Withstanding Voltage: AC 600 Vrms

The soldering heat is 260 deg for 5 Seconds

NO OF CONTACT	A±0.2	B±0.2	C±0.1	D±0.1	E±0.2
20	15.66	15.66	5.08	5.08	17.28
28	18.20	18.20	7.62	7.62	20.87
32	18.20	20.74	7.62	10.16	23.15
44	23.28	23.28	12.70	12.70	28.05
52	25.82	25.82	15.24	15.24	31.65
68	30.90	30.90	20.32	20.32	38.83
84	35.98	35.98	25.40	25.40	46.00

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE


SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION



煜倫股份有限公司

www.morethanall.com

DESCRIPTION: