



- NOTES:
- 1) Material :
Housing : Thermoplastic UL94V-0
Contact : BERYLLIUM C17200R-H,T=0.10mm.
 - 2) Plating :
Contact Plating - Gold over 45u" MIN.Nickel
Solder Tail Plating - Gold Flash over 45u" MIN.Nickel
 - 3) Contact Forces :
Max. 0.5 N For 0.5mm Contact Deflection.
Min. 0.25 N For 0.5mm Contact Deflection.
 - 4) Specification :
Withstanding Voltage:500V AC initial and 250 V AC final at sea level for 1 Minute
Insulation Resistance:1000M Ohms
Voltage Rating:5 Volts Max
Current Rating:10mA Max
Contact Resistance:30m Ohms Max
Operating Temperature:-40°C~+85°C
Insertion Cycles:20,000 Times
 - 5) Application:
For SIM Card Use Only

SCX-W1505X-06-LF
LEADFREE
RoHS Compliant



PART NO. SCX-W1505X-06

DWG NO. SCX-W1505X-06

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司