



Recommended P.C.B Layout

MATERIAL

Insulator : NYLON 46
Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C

PA-R20-1Xxx-LF
LEADFREE
1X02~1X33 WAY
(02) ~ (33)

RoHS Compliant

POLES	DIM E	POLES	DIM E
2	1.27	18	21.59
3	2.54	19	22.86
4	3.81	20	24.13
5	5.08	21	25.40
6	6.35	22	26.67
7	7.62	23	27.94
8	8.89	24	29.21
9	10.16	25	30.48
10	11.43	26	31.75
11	12.70	27	33.02
12	13.97	28	34.29
13	15.24	29	35.56
14	16.51	30	36.83
15	17.78	31	38.10
16	19.05	32	39.37
17	20.32	33	40.64



PART NO. PA-R20-1Xxx

DWG NO. PA-R20-1Xxx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.0 =±.30
.00 =±.15
.000 =±.XXX
.0000=±.
ANG.=±3°

DESCRIPTION:

PIN HEADER 1.27*1.27mm
RIGHT ANGLE TYPE, SINGLE ROW

AREA

REVISIONS

HK

DATE

煜倫股份有限公司