



SPECIFICATIONS

Material  
 Insulator: PBT, glass reinforced, rated UL 94V-0  
 Contact: Phosphor Bronze or Brass  
 Electrical  
 Current Rating: 1 Amp  
 Current Resistance: 30m ohm max.  
 Insulation Resistance: 3000 M OHM min.  
 Dielectric Withstanding Voltage: 500V AC for 1 minute  
 Operating Temperature: -40°C to +105°C  
 \* Terminated with 1.27mm pitch flat ribbon cable

E-C2FE-xx-LF  
 LEADFREE

RoHS Compliant

POSITION	A	B	C	D
10	43.06	10.16		22.36
14	48.14	15.24		27.44
16	50.68	17.78		29.98
20	55.76	22.86		35.06
26	63.38	30.48		42.68
34	73.54	40.64		52.84
40	81.16	48.26		60.46
50	93.86	60.96		73.16
60	106.56	73.66		85.86
62	109.10	76.20		88.40
64	111.64	78.74		90.94



PART NO. E-C2FE-xx

DWG NO. E-C2FE-xx

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE  
 .X ± 0.2  
 .XX ±  
 .XXX ±  
 AWG

DESCRIP TION: Edge card idc type with mouting ear 2.54mm

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

AREA	REVISIONS	HK	DATE	
------	-----------	----	------	--