



NOTE:

1. 100% OPEN & SHORT TEST
2. 200AC 2mA MAX/0.02S
3. 300DC 0.02SEC 10MΩ
4. CONTACT RESISTANCE: 3Ω MAX

5	H.S TUBE	H. S TUBE:OD:1.0mm BLACK	A/R	PCS
4	PE	PE	A/R	G
3	PVC	PVC-45/BLACK	A/R	G
2	DC 3.5 ST PLUG	ST 3.5 PLUG BLACK / Ni PLATED	1	PCS
1	CABLE	UL2547 (17/0.16C*3C+28S/0.10BC)*1C OD:3.5/BLACK	A/R	M
ITEM	NAME	DESCRIPTION	Q'TY	UNIT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

PNX1-030022-M100N-LF

SERIES | MALE | LEADFREE
22 AWG | 2540mm
03 WAY

DESCRIPTION: DC3.5 ST CABLE ASSEMBLY